

Evaluating Changing Sediment Contamination Conditions, Santa Monica Bay

Homa Lee¹, Steven Weisberg², Steven Bay², Clark Alexander³, Brian Edwards¹, Eddie Zeng², Masahiro Dojiri⁴, Marlene Noble¹, and Megan McQuarrie¹

The Southern California Coastal Water Research Project, the City of Los Angeles, and the United States Geological Survey are collaborating to investigate sediment pollution on the floor of Santa Monica Bay, offshore of the greater Los Angeles metropolitan area.


The Setting:



ABSTRACT

Santa Monica Bay, offshore of the greater Los Angeles metropolitan area, receives surface runoff, sewage, and industrial drainage. Recent surveys have shown that more than 95% of the area in the Bay has contaminates at concentrations exceeding the Effects Range Low (ER-L) threshold, a level at which biological effects begin to We conducted a study of the sediment on the floor of Santa Monica Bay to determine the severity of present contamination conditions and how levels of contamination have changed over the period during which Los Angeles was industrialized (approximately 1900 to the present). We obtained a set of box core samples at station locations defined using a stratified random design. Sediment samples were dated using short-half life radioisotopes (Pb-210) to define five time lines extending back over the last 100 years. Sediment from each of these time lines was tested for chlorinated hydrocarbons, metals and toxicity, as well as texture and physical properties. Analysis of these data show that, although surface sediment in the bay is still contaminated, contamination levels in the past were even greater. Overall conditions of sediment contamination in the Bay are improving. In addition, sediment data are combined with monitoring of currents and bottom boundary layer conditions to better understand patterns and rates of sediment and contaminant transport in the Bay. Our goal is to determine the geographic and stratigraphic distribution of contaminated marine sediment and to develop a predictive model for improving environmental management of this urban, coastal ocean. Ongoing studies of the mineralogy and organic chemistry of sediment samples are designed to assess the provenance and relative importance of inputs from several coastal streams, bluffs, and anthropogenic sources.

Sediment Monitoring:




Current Monitoring:

Predicting the fate of contaminated sediment grains requires an understanding of regional current patterns as well as the characteristics of water flow within a few meters of the seafloor. Long-term measurements of currents, wind stress, and the associated wave climate are needed to design predictive sediment transport and dispersal models. A current mooring was in place during the 1997-1998 El Nino winter off Marina del Rey to address these issues. Additional current moorings and benthic tripod were installed in December 1998 and will remain in place through the winter. Current moorings measure conditions such as currents, temperature, salinity and water quality throughout the water column. The benthic tripod measures similar conditions near the seafloor.

Current mooring USGS GEOPROBE (Benthic Tripod) temperature salinity LED = Infrared LED transmissometer water clarit CTD = Conductivity/Temperature/Depth recorder SED = Suspended sediment sample intake nozzle elastic tether current temperature current temperature EMCM (93.5) SED (92.5) salinity acoustic release EMCM (25) SED (24.5) (Instrument heights are in centimeters above bottom)

Core Profiles:




Sediment samples are dated, using short-half-life radioisotopes (Pb-210), along five time lines- 1900, prior to industrial development; 1945, a time of increasing development in the Los Angeles Basin; 1970, when sediment contamination was thought to be severe; 1985, following efforts to reduce contaminants in the bay; and 1997/1998 when the cores were taken.

Samples are tested for physical and textural properties (e.g. bulk density, velocity, magnetic susceptibility, and acoustic impedance) as well as for chlorinated hydrocarbons, metals and toxicity. The results are referenced to the lead-210 dating information.

Toxicity measurements are a standardized way to evaluate the impact of contaminated sediment on marine organisms. Two toxicity tests were used to evaluate the 26 box cores collected in 1997. An amphipod survival test was used to measure the toxicity of the sediment, and a sea urchin fertilization test was used to measure the toxicity of substances released from the sediment. To the left is a representation of both physical and toxicity tests from core 10B1 (green square on the above map) located near the historical discharge of sewage sludge (1957-1987) from the City of Los Angeles Hyperion Treatment Plant.

Both the amphipod survival and sea urchin fertilization tests detected toxicity in the core sections. The lowest levels occurred prior to 1950, before the initiation of wastewater disposal through Hyperion's outfall in 60 m of water, and after 1985, when steps were taken to reduce contamination levels. The results show that toxicity has been decreasing over the last two decades, suggesting improved contamination conditions.

GIS Maps:



Data from sediment samples (locations shown as dots) are presented as GIS layers that can be used in further analysis. An initial layer shows the variation of surficial density over Santa Monica Bay. The density data were obtained through gammaray logging of whole cores and represent a depth of 15 cm in the sediment column. Greater densities typically correspond to coarser sediment.

1 USGS, 345 Middlefield Road, MS 999, Menlo Park, CA 94025; 2 Skidaway Institute of Oceanography, 10 Ocean Science Circle, Savannah, GA, 31411; 3 Southern California Coastal Water Research Project, 7171 Fenwick Lane, Westminster, CA 92683; 4 City of Los Angeles, Los Angeles CA